



PLAN

INFRA-RISER® FOR MANHOLE			
WEIGHT (LBS.)	THICKNESS	INNER (W)	OUTER (H)
8	VARIES	26"	34"
16			
32			

1. CONTRACTOR TO INSTALL BRICK AND APPLY MORTAR BETWEEN THE RISER AND THE CONCRETE MANHOLE AS NECESSARY.
2. RUBBER MANHOLE RISERS SHALL BE MINIMUM 80% BY WEIGHT RECYCLED RUBBER AND MINIMUM 10% BY VOLUME, RECYCLED RFL COATED FIBER. ALL RUBBER MANHOLE RISERS SHALL MEET THE MINIMUM PHYSICAL PROPERTY STANDARDS EQUAL TO THAT OF THE INFRA-RISER® RUBBER COMPOSITE ADJUSTMENT RISERS AS MANUFACTURED AND SUPPLIED BY EJ.

Location:Filename: V:\eng\ACAD_STD\Technical Details\B-30 - Manhole Riser.dwg
 Plotted on: Wednesday, April 4, 2018 - 11:40 AM by Donchoe, William



Boston Water and Sewer Commission
 980 HARRISON AVE., BOSTON, MA 02119
 (617) 989-7000 www.bwsc.org

MANHOLE RISER
 Scale: Not To Scale

DATE:
 Mar. 27, 2018

DETAIL NO.
B-30